



Dexing Magnet Tech. Co., Ltd

The High Power Magnetizing Power

The table of model						
Model	DX-4030-30	DX-4060-30	DX-40120-30	DX-40180-30	DX-40240-30	DX-40300-30
Input Power	AC220V 50~60Hz 60A		AC380V 50~60Hz 60A			
Max Output Current	30,000		30,000			
Charge Voltage	DC200~4000V		DC200~4000V			
Repeat Precision of Charge Voltage	±1V+1digit		±1V+1digit			
Charge Time	12 (sec)	24 (sec)	16 (sec)	24 (sec)	32 (sec)	40 (sec)
The Capacity of Condenser	3,000uF	6,000uF	12,000uF	18,000uF	24,000uF	30,000uF
The Capacity Changing	1,000/2,000/ 3,000	1,000/2,000/ 6,000	1,000/2,000/6,000 / 12,000	1,000/2,000/6,000 / 12,000/18,000	1,000/2,000/6,000/ 12,000/18,000/24,000	1,000/2,000/6,000/ 12,000/18,000/24,000 / 30,000

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>

Dexing Magnet Tech. Co., Ltd

Main Switch	SCR			SCR		
Discharge Ampere Meter (Compare Function)	Have			Have		
Interior Discharge Circuit	Have			Have		
Enclosure Dimensions	1000W×1000D×200 OH	1660W×1000D×200 OH	3000W×1000D×200 OH	2000W×2000D×200 OH	3000W×2000D×2000 H	3000W×3000D×2000H
Weight	1200Kg	1800Kg	3600Kg	4800Kg	6000Kg	7200Kg

Add: No.86-101,RD West Jinshan, Huli Dist, Xiamen, China Zip code: 361009

Tel: 86-592-5237772

Fax: 86-592-5237901

Email:sales@magnetsource.com.cn, dexing2007@gmail.com

Home page:<http://www.magnetsource.com.cn> <http://www.magnetomachinery.com> <http://www.rubber-magnet.com>